## NSN 4810-00-884-8510

Solenoid Valve - Page 1 of 2

Thread Class: 3b 1st end

Poppet

Thread Direction:
Right-hand 1st end
Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4810-00-884-8510

| Flow Control Device Normal Operation Position:        |
|---|
| Open  |
| Maximum Operating Temp:                               |
| 275.0 degrees fahrenheit single response              |
| Connection Style:                                     |
| G4 gasket sea (boss) 1st end                          |
| Current Rating In Amps:                               |
| 0.400   |
| Valve Operation Method:                               |
| Solenoid  |
| Connection Type:                                      |
| Threaded internal boss 1st end                        |
| Mounting Position:                                    |
| Horizontal or vertical                                |
| Thready Qty Per Inch (tpi):                           |
| 18 1st end  |
| Maximum Operating Pressure:                           |
| 1200.0 pounds per square inch single response         |
| Thread Size:  |
| 0.562 inches 1st end                                  |
| Voltage In Volts And Current Type:                    |
| 115.0 ac  |
| Outside Diameter Tube Accommodated:                   |
| 0.375 inches 1st end                                  |
| Phase:  |
| Single  |
| Frequency In Hertz:                                   |
| 400.0   |
| Material:   |
| Aluminum alloy seat                                   |
| Media For Which Designed:                             |
| Hydraulic fluid, phosphate-ester base single response |
| Style Designator:                                     |
| Err-090   |
| Thread Series Designator:                             |
| Unjf 1st end  |
|   |
|   |

## NSN 4810-00-884-8510

Solenoid Valve - Page 2 of 2



| Shelf | LIIE. |
|-------|-------|
|       |       |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0