NSN 4810-00-886-3044

Solenoid Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4810-00-886-3044

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device Normal Operation Position:

Open

Connection Style:

G4 gasket sea (boss) 1st end

Current Rating In Amps:

29.000

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

14 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.875 inches 1st end

Seat Angle:

60.0 degrees 1st end

Voltage In Volts And Current Type:

29.0 dc

Outside Diameter Tube Accommodated:

0.625 inches 1st end

Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

Style Designator:

A6 straight through w/offset

Test Data Document:

18876-9194240 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0