NSN 4810-00-895-9148

Solenoid Valve - Page 1 of 2



Thread Class:
3b all ends
Thread Direction:
Right-hand all ends
Offset Distance:
0.562 inches
Flow Control Device Normal Operation Position:
Closed
Maximum Operating Temp:
160.0 degrees fahrenheit single response
End Application:
M110 howitzer family
Connection Style:
G4 gasket sea (boss) all ends
Current Rating In Amps:
1.600
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal boss all ends
Mounting Position:
Horizontal or vertical
Inlet/outlet Operating Pressure Differential:
Inlet/outlet Operating Pressure Differential: Between 0.000 pounds per square inch and 3000.0 pounds per square inch
Between 0.000 pounds per square inch and 3000.0 pounds per square inch
Between 0.000 pounds per square inch and 3000.0 pounds per square inch Maximum Operating Pressure:
Between 0.000 pounds per square inch and 3000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch single response
Between 0.000 pounds per square inch and 3000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size:
Between 0.000 pounds per square inch and 3000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.750 inches all ends
Between 0.000 pounds per square inch and 3000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.750 inches all ends Voltage In Volts And Current Type:
Between 0.000 pounds per square inch and 3000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.750 inches all ends Voltage In Volts And Current Type: 18.0 dc and 30.0 dc
Between 0.000 pounds per square inch and 3000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.750 inches all ends Voltage In Volts And Current Type: 18.0 dc and 30.0 dc Special Features:
Between 0.000 pounds per square inch and 3000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.750 inches all ends Voltage In Volts And Current Type: 18.0 dc and 30.0 dc Special Features: Spring loaded
Between 0.000 pounds per square inch and 3000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.750 inches all ends Voltage In Volts And Current Type: 18.0 dc and 30.0 dc Special Features: Spring loaded Media For Which Designed:
Between 0.000 pounds per square inch and 3000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.750 inches all ends Voltage In Volts And Current Type: 18.0 dc and 30.0 dc Special Features: Spring loaded Media For Which Designed: Hydraulic fluid, petroleum base single response
Between 0.000 pounds per square inch and 3000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.750 inches all ends Voltage In Volts And Current Type: 18.0 dc and 30.0 dc Special Features: Spring loaded Media For Which Designed: Hydraulic fluid, petroleum base single response Style Designator:
Between 0.000 pounds per square inch and 3000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.750 inches all ends Voltage In Volts And Current Type: 18.0 dc and 30.0 dc Special Features: Spring loaded Media For Which Designed: Hydraulic fluid, petroleum base single response Style Designator: A6 straight through w/offset
Between 0.000 pounds per square inch and 3000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.750 inches all ends Voltage In Volts And Current Type: 18.0 dc and 30.0 dc Special Features: Spring loaded Media For Which Designed: Hydraulic fluid, petroleum base single response Style Designator: A6 straight through w/offset Thread Series Designator:
Between 0.000 pounds per square inch and 3000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.750 inches all ends Voltage In Volts And Current Type: 18.0 dc and 30.0 dc Special Features: Spring loaded Media For Which Designed: Hydraulic fluid, petroleum base single response Style Designator: A6 straight through w/offset Thread Series Designator: Unf all ends

N/a

NSN 4810-00-895-9148

Solenoid Valve - Page 2 of 2



		eas	

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0