## NSN 4810-00-900-5965

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-900-5965	
Aperture Diameter:	
0.100 inches	
Flow Control Device Normal Operation Position:	
Closed	
Bolt Hole Quantity:	
4 2nd end	
Maximum Operating Temp:	
67.0 degrees fahrenheit single response	
Connection Style:	
Plain (tube) 1st end	
Width:	
1.380 inches 2nd end	
Length:	
1.380 inches 2nd end	
Current Rating In Amps:	
1.000	
Valve Operation Method:	
Solenoid	
Flange Shape:	
Rectangular 2nd end	
Connection Type:	
Unthreaded internal tube 1st end	
Maximum Operating Pressure:	
225.0 pounds per square inch single response	
Voltage In Volts And Current Type:	
23.0 dc and 30.0 dc	
Thickness:	
0.190 inches 2nd end	
Center To Center Distance Between Bolt Holes Along Length:	
1.062 inches 2nd end	
Center To Center Distance Between Bolt Holes Along Width:	
1.062 inches 2nd end	
Flange Face Design:	
Plain 2nd end	
Outside Diameter Tube Accommodated:	
1.000 inches 1st end	
Special Features:	
Keyway in electrical receptacle opposite to flow	
Media For Which Designed:	
Air single response	
Style Designator:	

Err-090

## NSN 4810-00-900-5965

Solenoid Valve - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0