

View Online at <https://aerobasegroup.com/nsn/4810-00-901-2806>

Thread Class:

3b

End Connection Quantity:

2

Valve Discharge Flow Rate:

1.2 gallons per minute

End Application:

T.O. 9h8-14-267-3 fig 4

Current Rating In Amps:

1.5

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal boss

Maximum Operating Pressure And Media For Which Designed:

3000.0 pounds per square inch hydraulic fluid, petroleum base

Thread Size:

0.438 inches

Body Material:

Aluminum alloy

Maximum Operating Temperature And Media For Which Designed:

275.0 degrees fahrenheit hydraulic fluid, petroleum base

Voltage In Volts And Current Type:

30.0 dc

Spool Position Quantity:

3

Spool Quantity:

1

Special Features:

Manufacturers suggested name is valve - hydraulic, solenoid selector; cylinder port pressures: operating 300 to 3000 psig, proof 4500 psig, burst 7500 psig; return port pressures: operating 1000 psig, proof 1500 psig, burst 2500 psig; operating medium mil-h-83282 or mil-h-46170; fluid & ambient temperature range -65 to + 275 degrees feh; dry wt 0.90 lbs max; this is a 4 way, 2 position valve; threads per ms33649-4

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A506h0