

View Online at <https://aerobasegroup.com/nsn/4810-00-907-0361>

**Maximum Operating Temp:**

600.0 degrees fahrenheit single response

**Minimum Operating Temp:**

-65.0 degrees fahrenheit

**Current Rating In Amps:**

1.000

**Valve Operation Method:**

Solenoid

**Flange Shape:**

Round 1st end

**Connection Type:**

Flange 1st end

**Features Provided:**

Manual override

**Maximum Operating Pressure:**

48.0 pounds per square inch single response

**Voltage In Volts And Current Type:**

20.0 dc and 29.0 dc

**Flange Face Design:**

Plain 1st end

**Special Features:**

Manufacturers suggested name is valve assembly, starter-control; ambient temp -65 to +400 degrees feg; pressures: proof 120 psig, burst 180 psig; duty cycle continuous from 20 to 29 vdc at +400 degrees feh; current drain 1.0 amps at 20 vdc; wt 4.1 lbs

**Material:**

Aluminum alloy body

**Media For Which Designed:**

Air single response

**Style Designator:**

Err-090

**Furnished Items And Quantity:**

1 filter and 1 filter screen

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A046b0