## NSN 4810-00-907-0663

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-907-0663

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Aperture Diameter:
0.250 inches
Flow Control Device:
Plug
Flow Control Device Normal Operation Position:
Closed
Maximum Operating Temp:
160.0 degrees fahrenheit single response
Connection Style:
G4 gasket sea (boss) 1st end
Current Rating In Amps:
1.000
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss 1st end
Mounting Position:
Horizontal
Thready Qty Per Inch (tpi):
20 1st end
Power Drive Operating Pressure:
3000.0 pounds per square inch
Inlet/outlet Operating Pressure Differential:
Between 1000.0 pounds per square inch and 3000.0 pounds per square inch
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.438 inches 1st end
Voltage In Volts And Current Type:
18.0 dc and 30.0 dc
Outside Diameter Tube Accommodated:
0.250 inches 1st end
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Style Designator:
A1 straight thru
Thread Series Designator:
Unf 1st end

## NSN 4810-00-907-0663

Solenoid Valve - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0