

View Online at <https://aerobasegroup.com/nsn/4810-00-915-5873>

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Piston

**Flow Control Device Normal Operation Position:**

Closed

**Maximum Operating Temp:**

200.0 degrees fahrenheit single response

**Connection Style:**

G45 flareless (tube) 2nd end

**Current Rating In Amps:**

0.875

**Valve Operation Method:**

Solenoid

**Connection Type:**

Threaded external tube 2nd end

**Mounting Position:**

Horizontal

**Thready Qty Per Inch (tpi):**

24 1st end

**Maximum Operating Pressure:**

350.0 pounds per square inch single response

**Thread Size:**

0.312 inches 1st end

**Voltage In Volts And Current Type:**

14.0 dc and 30.0 dc

**Outside Diameter Tube Accommodated:**

0.250 inches 2nd end

**Material:**

Steel comp 303 flow control device

**Material Specification:**

66 federal standard single material response flow control device

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Style Designator:**

Err-090

**Thread Series Designator:**

Unjf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0