NSN 4810-00-922-0252

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-922-0252

| Thread Class: |
|--|
| 3b all ends |
| Thread Direction: |
| Right-hand all ends |
| Offset Distance: |
| 1.126 inches |
| Flow Control Device: |
| Poppet |
| Flow Control Device Normal Operation Position: |
| Open |
| Connection Style: |
| G4 gasket sea (boss) all ends |
| Current Rating In Amps: |
| 0.260 |
| Valve Operation Method: |
| Solenoid |
| Connection Type: |
| Threaded internal boss all ends |
| Mounting Position: |
| Horizontal |
| Thready Qty Per Inch (tpi): |
| 12 all ends |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch single response |
| Thread Size: |
| 1.062 inches all ends |
| Voltage In Volts And Current Type: |
| 115.0 ac |
| Outside Diameter Tube Accommodated: |
| 0.750 inches all ends |
| Phase: |
| Single |
| Frequency In Hertz: |
| 60.0 |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Style Designator: |
| Err-090 |
| Thread Series Designator: |
| Unj all ends |
| Shelf Life: |
| |
| N/a |

NSN 4810-00-922-0252

Solenoid Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

