NSN 4810-00-924-4892

Solenoid Valve - Page 1 of 2

Pipe Size Accommodated:



View Online at https://aerobasegroup.com/nsn/4810-00-924-4892

0.250 inches all ends
Thread Direction:
Right-hand all ends
Aperture Diameter:
0.188 inches
Flow Control Device:
Piston
Flow Control Device Normal Operation Position:
Closed
Renewable Seat Ring Type:
Pressed-in
Connection Style:
G9 plain, optional en (pipe) all ends
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal pipe all ends
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
18 all ends
Maximum Operating Pressure:
5000.0 pounds per square inch single response
Thread Size:
0.250 inches all ends
Voltage In Volts And Current Type:
110.0 ac
Phase:
Single
Frequency In Hertz:
50.0
Material:
Stainless steel flow control device
Media For Which Designed:
Media For Which Designed: Water-oil-gas single response
<u>-</u>
Water-oil-gas single response
Water-oil-gas single response Surface Treatment:
Water-oil-gas single response Surface Treatment: Passivate
Water-oil-gas single response Surface Treatment: Passivate Style Designator:
Water-oil-gas single response Surface Treatment: Passivate Style Designator: Err-090

NSN 4810-00-924-4892

Solenoid Valve - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0