Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-939-0260

View Online at https://aerobasegroup.com/nsn/4810-00-939-0260
Thread Class:
3b all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Needle or stem
Flow Control Device Normal Operation Position:
Open
Maximum Operating Temp:
250.0 degrees fahrenheit 2nd response
End Application:
Aircraft, hercules c-130; aircraft, galaxy c-5; aircraft, thunderbolt ii, a-10; aircraft, b-1b; aircraft, (ac-130h, mc-130h, ec-130e, hc-130
en
Connection Style:
G4 gasket sea (boss) all ends
Current Rating In Amps:
0.400
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal boss all ends
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
15.0 pounds per square inch single response
Thread Size:
0.437 inches all ends
Voltage In Volts And Current Type:
28.0 dc
Outside Diameter Tube Accommodated:
0.250 inches all ends
Material:
Stainless steel body
Media For Which Designed:
Air single response
Style Designator:
Err-090
Thread Series Designator:
Unjf all ends
Shelf Life:
N/a

Unit Of Measure:

## NSN 4810-00-939-0260

Solenoid Valve - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A046b0

