NSN 4810-00-955-6651

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-955-6651 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends **Aperture Diameter:** 0.125 inches Flow Control Device: **Poppet** Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 225.0 degrees fahrenheit single response **Connection Style:** G42 flared (tube) all ends **Current Rating In Amps:** 0.234 **Valve Operation Method:** Solenoid **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical **Inlet/outlet Operating Pressure Differential:** 2.0 pounds per square inch **Maximum Operating Pressure:** 400.0 pounds per square inch single response **Thread Size:** 0.438 inches all ends Seat Angle: 37.0 degrees all ends **Voltage In Volts And Current Type:** 120.0 ac Phase: Single **Special Features:** Class b potted coil Frequency In Hertz: 60.0 Material: Stainless steel flow control device

Media For Which Designed:
Refrigerant 12 single response

NSN 4810-00-955-6651

Solenoid Valve - Page 2 of 2



Style Designator:
Err-090
Thread Series Designator:
Unf all ends
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0