

View Online at <https://aerobasegroup.com/nsn/4810-00-961-1680>

**Body Material:**

Steel, corrosion resisting

**Outside Surface Treatment:**

Passivated

**Body Style:**

Tee

**Stem Material:**

Steel, corrosion resisting

**Media For Which Designed:**

Hydraulic fluid, phosphate-ester base

**First End Connection Type:**

Threaded internal boss

**First End Style Designator:**

Gasket seal

**First End Thread Size And Series/type Designator:**

1 1/16-12 un

**First End Thread Class:**

3b

**First End Thread Direction:**

Right-hand

**Second End Relationship With First End:**

Identical

**Third End Relationship With Preceding Ends:**

Identical with first end

**Seat Material:**

Steel, corrosion resisting

**Packing Material:**

Rubber, synthetic

**Flow Control Device:**

Piston, free type

**Flow Control Device Material:**

Steel, corrosion resisting

**End Connection Quantity:**

3

**Renewable Seat Ring Type:**

Pressed-in

**Mounting Facility:**

Bolts

**Outlet Pressure Range:**

+35.0/+150.0 pounds per square inch

**Regulation Type:**

Automatic single stage

**Valve Loading Method:**

Spring

**Remote Actuation Method:**

Solenoid

**Maximum Inlet Pressure Rating:**

3000.0 pounds per square inch

**Filter:**

Not included

**Temperature Rating:**

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A21100