NSN 4810-00-974-1229

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-974-1229 **Thread Direction:** Right-hand all ends **Aperture Diameter:** 0.625 inches Flow Control Device: Diaphragm Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 180.0 degrees fahrenheit single response **Connection Style:** G9 plain, optional en (pipe) all ends **Current Rating In Amps:** 0.052 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 18 all ends **Inlet/outlet Operating Pressure Differential:** 200.0 pounds per square inch **Maximum Operating Pressure:** 300.0 pounds per square inch single response **Thread Size:** 0.375 inches all ends **Voltage In Volts And Current Type:** 115.0 ac Phase: Single Rubber butadiene-acrylonitrile class nbr seat

Frequency In Hertz: 60.0 Material: Media For Which Designed: Water-oil-gas single response **Style Designator:** Err-090 **Thread Series Designator:** Npt all ends

NSN 4810-00-974-1229

Solenoid Valve - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0