NSN 4810-00-977-9050

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-977-9050 **Aperture Diameter:** 0.625 inches **Flow Control Device:** Needle or stem Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 77.0 degrees fahrenheit single response **Connection Style:** Plain (tube) all ends **Current Rating In Amps:** 0.091 **Valve Operation Method:** Solenoid **Connection Type:** Unthreaded internal tube all ends **Mounting Position:** Horizontal or vertical **Inlet/outlet Operating Pressure Differential:** 50.0 pounds per square inch **Maximum Operating Pressure:** 150.0 pounds per square inch single response **Voltage In Volts And Current Type:** 115.0 ac **Outside Diameter Tube Accommodated:** 0.500 inches all ends Phase: Single **Special Features:** Furnished w/manual operator, solenoid assembly high shock per mil-s-901 w/class f or h insulation w/submersible cover Frequency In Hertz: 60.0 Material: Plastic polytetrafluoroethylene flow control device **Style Designator:** Err-090 Shelf Life: N/a

Demilitarization: No

Unit Of Measure:

NSN 4810-00-977-9050

Solenoid Valve - Page 2 of 2



Fiig:

A046b0