NSN 4810-00-977-9050

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-977-9050

Aperture Diameter:

0.625 inches

Flow Control Device:

Needle or stem

Flow Control Device Normal Operation Position:

Closed

Maximum Operating Temp:

77.0 degrees fahrenheit single response

Connection Style:

Plain (tube) all ends

Current Rating In Amps:

0.091

Valve Operation Method:

Solenoid

Connection Type:

Unthreaded internal tube all ends

Mounting Position:

Horizontal or vertical

Inlet/outlet Operating Pressure Differential:

50.0 pounds per square inch

Maximum Operating Pressure:

150.0 pounds per square inch single response

Voltage In Volts And Current Type:

115.0 ac

Outside Diameter Tube Accommodated:

0.500 inches all ends

Phase:

Single

Special Features:

Furnished w/manual operator, solenoid assembly high shock per mil-s-901 w/class f or h insulation w/submersible cover

Frequency In Hertz:

60.0

Material:

Plastic polytetrafluoroethylene flow control device

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 4810-00-977-9050

Solenoid Valve - Page 2 of 2

Fiig: A046b0

