## NSN 4810-00-991-9146

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-991-9146
Pipe Size Accommodated:
0.250 inches 2nd end
Thread Class:
3b 2nd end
Thread Direction:
Right-hand 1st end
Aperture Diameter:
0.051 inches
Flow Control Device:
Disk
Flow Control Device Normal Operation Position:
Closed
Renewable Seat Ring Type:
Pressed-in
Connection Style:
G4 gasket sea (boss) 2nd end
Current Rating In Amps:
1.500
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal boss 2nd end
Mounting Position:
Horizontal
Thready Qty Per Inch (tpi):
20 2nd end
Inlet/outlet Operating Pressure Differential:
5.0 pounds per square inch
Maximum Operating Pressure:
300.0 pounds per square inch single response
Thread Size:
0.438 inches 2nd end
Seat Angle:
37.0 degrees 1st end

**Voltage In Volts And Current Type:** 

14.0 dc and 30.0 dc

**Outside Diameter Tube Accommodated:** 

0.250 inches 1st end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Style Designator:

Err-090

## NSN 4810-00-991-9146

Solenoid Valve - Page 2 of 2



Thread	<b>Series</b>	Design	nator:
	0000	-00.9.	

Unjf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0