NSN 4810-00-995-1132

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-995-1132 **Thread Direction:** Right-hand all ends **Aperture Diameter:** 0.094 inches Flow Control Device: Piston Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 230.0 degrees fahrenheit single response **Connection Style:** G9 plain, optional en (pipe) all ends **Current Rating In Amps:** 0.083 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal **Inlet/outlet Operating Pressure Differential:** 300.0 pounds per square inch **Maximum Operating Pressure:** 400.0 pounds per square inch single response **Thread Size:** 0.125 inches all ends **Voltage In Volts And Current Type:** 120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Stainless steel seat Media For Which Designed: Air 1st response **Surface Treatment: Passivate Style Designator:** Err-090 **Thread Series Designator:**

Npt all ends

NSN 4810-00-995-1132

Solenoid Valve - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0