NSN 4810-01-007-0536

Solenoid Valve - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/4810-01-007-0536

| Flow Control Device: |
|------------------------------------------------------------|
| Piston |
| Flow Control Device Normal Operation Position: |
| Open |
| Bolt Hole Quantity: |
| 4 1st end |
| Maximum Operating Temp: |
| 520.0 degrees fahrenheit single response |
| Width: |
| 1.750 inches 1st end |
| Length: |
| 1.750 inches 1st end |
| Current Rating In Amps: |
| 75.000 |
| Valve Operation Method: |
| Solenoid |
| Flange Shape: |
| Rectangular with holes 1st end |
| Connection Type: |
| Flange 1st end |
| Mounting Position: |
| Horizontal |
| Valve Size: |
| 0.940 inches |
| Maximum Operating Pressure: |
| 235.0 pounds per square inch single response |
| Voltage In Volts And Current Type: |
| 18.0 dc and 30.0 dc |
| Face To Face Distance: |
| 3.050 inches |
| Thickness: |
| 0.120 inches 1st end |
| Bolt Hole Diameter: |
| 0.218 inches 1st end |
| Center To Center Distance Between Bolt Holes Along Length: |
| 1.312 inches 1st end |
| Center To Center Distance Between Bolt Holes Along Width: |
| 1.312 inches 1st end |
| Flange Face Design: |
| Plain 1st end |
| Material: |
| Steel comp 630 flow control device |
| |

NSN 4810-01-007-0536

Solenoid Valve - Page 2 of 2

Media For Which Designed:

Air single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A046b0

