NSN 4810-01-017-3997

Solenoid Valve - Page 1 of 2

Thread Class: 3b all ends

Poppet

Thread Direction:
Right-hand all ends
Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4810-01-017-3997

Flow Control Device Normal Operation Position:
Closed
Maximum Operating Temp:
180.0 degrees fahrenheit single response
Connection Style:
G5a flar (tube) all ends
Current Rating In Amps:
1.000
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal tube all ends
Mounting Position:
Horizontal
Inlet/outlet Operating Pressure Differential:
300.0 pounds per square inch
Maximum Operating Pressure:
1000.0 pounds per square inch single response
Thread Size:
0.438 inches all ends
Seat Angle:
45.0 degrees all ends
Voltage In Volts And Current Type:
28.0 dc
Outside Diameter Tube Accommodated:
0.250 inches all ends
Special Features:
W/two mtg holes 0.219 in. Dia
Material:
Stainless steel flow control device
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Style Designator:
Err-090
Thread Series Designator:
Unjf all ends

NSN 4810-01-017-3997

Solenoid Valve - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0