

View Online at <https://aerobasegroup.com/nsn/4810-01-017-5072>

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**End Application:**

T.O. 6j15-10-238-3

**Connection Style:**

G4 gasket sea (boss) 1st end

**Connection Type:**

Threaded internal boss 1st end

**Mounting Position:**

Horizontal or vertical

**Special Features:**

Manufacturers suggested name is solenoid shutoff valve assembly; ambient operating temp 300 degrees f for 10 min., 360 degrees feh for 1 min. And -65 to +160 degrees feh continuous; operating fluid temp -65 to +180 degrees feh continuous; fluids media mil-g-5572, grade 115/145 diluted with 3% by volume with oil in accord with mil-I-22851 type ii, also mil-t-5624 grades jp4 & jp5 or jp8, and tt-s-735 0 to 30% aromatic content; operating pressure 30 psig, proof 120 psig, burst 180 psig

**Material:**

Aluminum alloy 2024 body

**Material Specification:**

Qq-a-225/6 federal specification single material response body

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Style Designator:**

Err-090

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A046b0

**Mil-std (military Standard):**

Mil-a-8625 spec.