

View Online at <https://aerobasegroup.com/nsn/4810-01-017-5072>

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

End Application:

T.O. 6j15-10-238-3

Connection Style:

G4 gasket sea (boss) 1st end

Connection Type:

Threaded internal boss 1st end

Mounting Position:

Horizontal or vertical

Special Features:

Manufacturers suggested name is solenoid shutoff valve assembly; ambient operating temp 300 degrees f for 10 min., 360 degrees feh for 1 min. And -65 to +160 degrees feh continuous; operating fluid temp -65 to +180 degrees feh continuous; fluids media mil-g-5572, grade 115/145 diluted with 3% by volume with oil in accord with mil-I-22851 type ii, also mil-t-5624 grades jp4 & jp5 or jp8, and tt-s-735 0 to 30% aromatic content; operating pressure 30 psig, proof 120 psig, burst 180 psig

Material:

Aluminum alloy 2024 body

Material Specification:

Qq-a-225/6 federal specification single material response body

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.