NSN 4810-01-019-4657

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-019-4657

Thread Direction:

Right-hand all ends

Aperture Diameter:

0.750 inches

Flow Control Device:

Disk

Flow Control Device Normal Operation Position:

Closed

Maximum Operating Temp:

180.0 degrees fahrenheit single response

Connection Style:

G9 plain, optional en (pipe) all ends

Current Rating In Amps:

0.500

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe all ends

Mounting Position:

Horizontal or vertical

Inlet/outlet Operating Pressure Differential:

Between 5.0 pounds per square inch and 125.0 pounds per square inch

Maximum Operating Pressure:

300.0 pounds per square inch single response

Thread Size:

0.750 inches all ends

Voltage In Volts And Current Type:

120.0 ac

Phase:

Single

Special Features:

Flow control is rubber, ehtylene propylene

Frequency In Hertz:

60.0

Material:

Rubber flow control device

Media For Which Designed:

Water, fresh single response

Style Designator:

Err-090

Thread Series Designator:

Npt all ends

NSN 4810-01-019-4657

Solenoid Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

