NSN 4810-01-020-5311

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-020-5311 **Thread Direction:** Right-hand all ends **Aperture Diameter:** 1.750 inches Flow Control Device: Disk Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 140.0 degrees fahrenheit single response **Connection Style:** G9 plain, optional en (pipe) all ends **Current Rating In Amps:** 0.050 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal or vertical **Inlet/outlet Operating Pressure Differential:** 125.0 pounds per square inch **Maximum Operating Pressure:** 300.0 pounds per square inch single response **Thread Size:** 2.000 inches all ends **Voltage In Volts And Current Type:** 120.0 ac Phase: Single **Special Features:** Explosion proof and waterright solenoid enclosure Frequency In Hertz: Rubber butadiene-acrylonitrile class nbr flow control device

60.0 Material: Media For Which Designed: Gas, inert 1st response **Style Designator:** Err-090 **Thread Series Designator:** Npt all ends

NSN 4810-01-020-5311

Solenoid Valve - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0