NSN 4810-01-020-7165

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-020-7165 **Aperture Diameter:** 0.375 inches Flow Control Device: Piston Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 285.0 degrees fahrenheit single response **Connection Style:** Socket (tube) all ends **Current Rating In Amps:** 0.359 **Valve Operation Method:** Solenoid **Connection Type:** Unthreaded internal tube all ends **Mounting Position:** Horizontal or vertical **Inlet/outlet Operating Pressure Differential:** 300.0 pounds per square inch **Maximum Operating Pressure:** 500.0 pounds per square inch single response **Voltage In Volts And Current Type:** 120.0 ac **Outside Diameter Tube Accommodated:** 0.625 inches all ends Phase: Single **Special Features:** Body tappep for mounting bracket Frequency In Hertz: 60.0 Material: Stainless steel flow control device Media For Which Designed: Refrigerant 12 single response **Style Designator:** Err-090 Shelf Life: N/a **Unit Of Measure:**

--

NSN 4810-01-020-7165

Solenoid Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0