

View Online at <https://aerobasegroup.com/nsn/4810-01-023-4879>

Pipe Size Accommodated:

1.000 inches 1st end

Thread Direction:

Right-hand 1st end

Aperture Diameter:

1.049 inches

Flow Control Device:

Disk

Flow Control Device Normal Operation Position:

Open

Renewable Seat Ring Type:

Pressed-in

Maximum Operating Temp:

200.0 degrees fahrenheit single response

Connection Style:

G9 plain, optional en (pipe) 1st end

Current Rating In Amps:

1.300

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe 1st end

Mounting Position:

Vertical

Power Drive Operating Pressure:

125.0 pounds per square inch

Inlet/outlet Operating Pressure Differential:

5.0 pounds per square inch

Maximum Operating Pressure:

250.0 pounds per square inch single response

Voltage In Volts And Current Type:

125.0 dc

Special Features:

Explosion proof-watertight solenoid enclosure design

Material:

Steel flow control device

Material Specification:

Rubber, buna-s assn standard single material response seat

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0