

View Online at <https://aerobasegroup.com/nsn/4810-01-026-3809>

Thread Class:

3a all ends

Thread Direction:

Right-hand all ends

Aperture Diameter:

Between 0.184 inches and 0.190 inches

Flow Control Device:

Piston

Flow Control Device Normal Operation Position:

Closed

Maximum Operating Temp:

200.0 degrees fahrenheit single response

Connection Style:

G45 flareless (tube) all ends

Current Rating In Amps:

0.320

Valve Operation Method:

Solenoid

Connection Type:

Threaded external tube all ends

Mounting Position:

Horizontal

Maximum Operating Pressure:

150.0 pounds per square inch single response

Thread Size:

0.437 inches all ends

Seat Angle:

12.0 degrees all ends

Voltage In Volts And Current Type:

24.0 dc

Outside Diameter Tube Accommodated:

0.250 inches all ends

Special Features:

Media is cleaning fluid. Surface treatment is electroless nickel plated

Material:

Steel comp 302 seat or steel comp 303 seat or steel comp 304 seat

Material Specification:

Fed standard 66, aisi 430f/sae 51430f federal standard 2nd material response flow control device

Surface Treatment:

Passivate

Style Designator:

Err-090

Thread Series Designator:

Unjf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0