NSN 4810-01-029-4800

Flow Control Device Normal Operation Position:

Solenoid Valve - Page 1 of 2

Thread Class: 3b 1st end

Piston

Thread Direction:
Right-hand 1st end
Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4810-01-029-4800

Closed
Maximum Operating Temp:
260.0 degrees fahrenheit single response
Connection Style:
G4 gasket sea (boss) 1st end
Current Rating In Amps:
1.000
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal boss 1st end
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
1200.0 pounds per square inch single response
Thread Size:
0.438 inches 1st end
Voltage In Volts And Current Type:
26.0 dc
Outside Diameter Tube Accommodated:
0.250 inches 1st end
Material:
Stainless steel flow control device
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Anodize
Style Designator:
Err-090
Thread Series Designator:
Unjf 1st end
Reference Number Differentiating Characteristics:
As differentiated by the source control dwg no.
Shelf Life:
N/a

NSN 4810-01-029-4800

Solenoid Valve - Page 2 of 2



		eas	

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0