NSN 4810-01-031-1753

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-031-1753 **Thread Direction:** Right-hand all ends **Aperture Diameter:** 0.062 inches Flow Control Device: Disk Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 180.0 degrees fahrenheit single response **Connection Style:** G9 plain, optional en (pipe) all ends **Current Rating In Amps:** 0.050 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal **Maximum Operating Pressure:** 125.0 pounds per square inch single response **Thread Size:** 0.250 inches all ends **Voltage In Volts And Current Type:** 120.0 ac Phase: Single **Special Features:** W/watertight and explosion proof solenoid enclosure Frequency In Hertz: 60.0 Material: Rubber butadiene-acrylonitrile class nbr flow control device Media For Which Designed: Water-oil-gas single response **Style Designator:** Err-090 **Thread Series Designator:**

Npt all ends Shelf Life:

N/a

NSN 4810-01-031-1753

Solenoid Valve - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A046b0