NSN 4810-01-038-1432

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-038-1432 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet** Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Connection Style:** G4 gasket sea (boss) all ends **Current Rating In Amps:** 1.000 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal boss all ends **Mounting Position:** Horizontal **Maximum Operating Pressure:** 20.0 pounds per square inch single response **Thread Size:** 0.875 inches 1st end **Voltage In Volts And Current Type:** 18.0 dc and 30.0 dc Material: Steel comp 304 **Material Specification:** Fed standard 66, aisi304/sae30304 federal standard single material response Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment: Passivate Style Designator:** Err-090 **Thread Series Designator:** Unjf all ends Shelf Life: N/a

Unit Of Measure:

NSN 4810-01-038-1432

Solenoid Valve - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A046b0