# NSN 4810-01-052-1254

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-052-1254

## Thread Direction:

Right-hand all ends

## **Flow Control Device:**

Disk

## Flow Control Device Normal Operation Position:

Closed

# Maximum Operating Temp:

180.0 degrees fahrenheit single response

#### **Connection Style:**

G9 plain, optional en (pipe) all ends

# Current Rating In Amps:

0.013

Valve Operation Method:

Solenoid

#### **Connection Type:**

Threaded internal pipe all ends

**Mounting Position:** 

Horizontal or vertical

# Maximum Operating Pressure:

200.0 pounds per square inch single response

## Thread Size:

0.250 inches all ends

#### Voltage In Volts And Current Type:

440.0 ac

## **Center To Center Distance:**

1.000 inches

Phase:

Single

#### **Frequency In Hertz:**

60.0

# Material:

Rubber butadiene-acrylonitrile class nbr flow control device

# Media For Which Designed:

Water-oil-gas single response

# Style Designator:

Err-090

# **Thread Series Designator:**

Npt all ends

Shelf Life:

N/a

# Unit Of Measure:

---

# NSN 4810-01-052-1254

Solenoid Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

