## NSN 4810-01-053-8312

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-053-8312 **Thread Direction:** Right-hand 3rd end Offset Distance: 1.000 inches Flow Control Device: Stem Flow Control Device Normal Operation Position: Closed **Connection Style:** G9 plain, optional en (pipe) 3rd end **Current Rating In Amps:** 0.050 **Valve Operation Method:** Solenoid **Connection Type:** Unthreaded external hose 1st end **Mounting Position:** Horizontal **Maximum Operating Pressure:** 30.0 pounds per square inch single response **Thread Size:** 0.125 inches 3rd end **Voltage In Volts And Current Type:** 110.0 ac and 120.0 ac **Inside Diameter Hose Accommodated:** 0.125 inches 1st end Phase: Single **Special Features:** Filter screen all ends Frequency In Hertz: 50.0 and 60.0 Material: Copper alloy Media For Which Designed: Air single response Style Designator: Err-090 **Thread Series Designator:** Npt 3rd end

Shelf Life:

N/a

## NSN 4810-01-053-8312

Solenoid Valve - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0