NSN 4810-01-060-5008

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-060-5008 **Thread Class:** 3b 2nd end **Thread Direction:** Right-hand 1st end **Aperture Diameter:** 0.125 inches Flow Control Device: **Poppet** Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 250.0 degrees fahrenheit single response **Connection Style:** G4 gasket sea (boss) 2nd end **Current Rating In Amps:** 1.000 **Valve Operation Method:** Electric motor **Connection Type:** Threaded internal boss 2nd end **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 5.0 pounds per square inch single response **Thread Size:** 0.437 inches 2nd end Seat Angle: 37.0 degrees 1st end **Voltage In Volts And Current Type:** 24.0 dc **Outside Diameter Tube Accommodated:** 0.250 inches 2nd end Material: Stainless steel Media For Which Designed: Fuel/oil, hydrocarbon single response Style Designator: Err-090 **Thread Series Designator:** Unjf 1st end

Shelf Life:

N/a

NSN 4810-01-060-5008

Solenoid Valve - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A046b0