## NSN 4810-01-063-4284

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-063-4284

| Flow Control Device:   |
|--|
| Disk   |
| Flow Control Device Normal Operation Position:                       |
| Open   |
| Bolt Hole Quantity:  |
| 3 all ends   |
| Valve Operation Method:  |
| Solenoid   |
| Flange Shape:  |
| Round with holes all ends  |
| Connection Type:   |
| Flange all ends  |
| Mounting Position:   |
| Horizontal   |
| Valve Size:  |
| 0.625 inches   |
| Maximum Operating Pressure:  |
| 700.0 pounds per square inch single response                         |
| Outside Diameter:  |
| 3.604 inches all ends  |
| Face To Face Distance:   |
| 5.008 inches   |
| Thickness:   |
| 0.695 inches all ends  |
| Bolt Hole Diameter:  |
| 0.550 inches all ends  |
| Bolt Circle Diameter:  |
| 2.454 inches all ends  |
| Flange Face Design:  |
| Plain all ends   |
| Special Features:  |
| Has automatic trip mechanism, manual override and position indicator |
| Material:  |
| Copper alloy body  |
| Media For Which Designed:  |
| Water, salt single response  |
| Style Designator:  |
| Err-090  |
| Shelf Life:  |
| N/a  |

**Unit Of Measure:** 

## NSN 4810-01-063-4284

Solenoid Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0