## NSN 4810-01-075-7228

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-075-7228

### Thread Direction:

Right-hand all ends

**Flow Control Device:** 

Piston

#### Flow Control Device Normal Operation Position:

Closed

#### Maximum Operating Temp:

180.0 degrees fahrenheit single response

#### **Connection Style:**

G9 plain, optional en (pipe) all ends

#### Current Rating In Amps:

0.088

#### Valve Operation Method:

Solenoid

#### Connection Type:

Threaded internal pipe all ends

#### **Mounting Position:**

Horizontal or vertical

### Inlet/outlet Operating Pressure Differential:

15.0 pounds per square inch

#### Maximum Operating Pressure:

150.0 pounds per square inch single response

#### Thread Size:

0.375 inches all ends

#### Voltage In Volts And Current Type:

120.0 ac

#### Phase:

Single

## Frequency In Hertz:

50.0

## Material:

Copper alloy body

## Media For Which Designed:

Water-oil-gas single response

## Style Designator:

Err-090

## Thread Series Designator:

Npt all ends

## Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 4810-01-075-7228

Solenoid Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

