

View Online at <https://aerobasegroup.com/nsn/4810-01-080-0471>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device Normal Operation Position:

Open

End Application:

T56-a9 eng, c-130 acft; applicable t.O. 6j15-4-28-3

Connection Style:

Flared (tube) 1st end

Valve Operation Method:

Solenoid

Connection Type:

Threaded external tube 1st end

Mounting Position:

Horizontal

Thready Qty Per Inch (tpi):

16 1st end

Thread Size:

0.750 inches 1st end

Seat Angle:

37.0 degrees 1st end

Voltage In Volts And Current Type:

14.0 dc and 30.0 dc

Outside Diameter Tube Accommodated:

0.500 inches 1st end

Special Features:

Manufacturers suggested name is drain valve assembly; o/a dimensions: length 4.66 in., width 2.69 in., depth 2.74 in.; inlet ports (2) 3/4-16 external thread for 1/2 in. Od tube; drain port 7/16-20 external thread for 1/4 in. Od tube

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Surface Treatment:

Passivate

Style Designator:

Caps w/offset

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0