## NSN 4810-01-080-0471



Solenoid Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4810-01-080-0471 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device Normal Operation Position: Open **End Application:** T56-a9 eng, c-130 acft; applicable t.O. 6j15-4-28-3 **Connection Style:** Flared (tube) 1st end **Valve Operation Method:** Solenoid **Connection Type:** Threaded external tube 1st end **Mounting Position:** Horizontal Thready Qty Per Inch (tpi): 16 1st end **Thread Size:** 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end **Voltage In Volts And Current Type:** 14.0 dc and 30.0 dc **Outside Diameter Tube Accommodated:** 0.500 inches 1st end **Special Features:** Manufacturers suggested name is drain valve assembly; o/a dimensions: length 4.66 in., width 2.69 in., depth 2.74 in.; inlet ports (2) 3/4-16 external thread for 1/2 in. Od tube; drain port 7/16-20 external thread for 1/4 in. Od tube Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment: Passivate Style Designator:** Caps w/offset **Thread Series Designator:** Unf 1st end Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 4810-01-080-0471

Solenoid Valve - Page 2 of 2



Fiig:

A046b0