## NSN 4810-01-100-3409

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-100-3409

#### Thread Direction:

Right-hand all ends

#### **Flow Control Device:**

Disk

### Flow Control Device Normal Operation Position:

Closed

#### Maximum Operating Temp:

500.0 degrees fahrenheit single response

#### **Connection Style:**

G9 plain, optional en (pipe) all ends

#### Current Rating In Amps:

0.700

Valve Operation Method:

Solenoid

#### Connection Type:

Threaded internal pipe all ends

**Mounting Position:** 

Horizontal

#### Maximum Operating Pressure:

600.0 pounds per square inch single response

#### Thread Size:

0.250 inches all ends

#### Voltage In Volts And Current Type:

115.0 ac

Phase:

Single

#### Frequency In Hertz:

60.0

#### Material:

Copper alloy body

#### Media For Which Designed:

Water-oil-gas single response

#### Style Designator:

Err-090

#### **Thread Series Designator:**

Npt all ends

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# **NSN 4810-01-100-3409** Solenoid Valve - Page 2 of 2

Fiig: A046b0

