## NSN 4810-01-106-2218

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-106-2218

| Pipe Size Accommodated:                        |
|--|
| 0.500 inches all ends                          |
| Aperture Diameter:                             |
| 0.062 inches                                   |
| Flow Control Device:                           |
| Disk   |
| Flow Control Device Normal Operation Position: |
| Open   |
| Maximum Operating Temp:                        |
| 180.0 degrees fahrenheit single response       |
| Connection Style:                              |
| Socket all ends                                |
| Current Rating In Amps:                        |
| 0.170  |
| Valve Operation Method:                        |
| Solenoid                                       |
| Connection Type:                               |
| Unthreaded internal pipe all ends              |
| Mounting Position:                             |
| Horizontal or vertical                         |
| Inlet/outlet Operating Pressure Differential:  |
| 125.0 pounds per square inch                   |
| Voltage In Volts And Current Type:             |
| 115.0 ac                                       |
| Phase:   |
| Single   |
| Special Features:                              |
| Submersible solenoid enclosure                 |
| Frequency In Hertz:                            |
| 60.0   |
| Material:                                      |
| Copper alloy body                              |
| Media For Which Designed:                      |
| Gas, inert 2nd response                        |
| Style Designator:                              |
| Err-090  |
| Shelf Life:                                    |
| N/a  |
| Unit Of Measure:                               |
|  |
| Demilitarization:                              |

No

## NSN 4810-01-106-2218

Solenoid Valve - Page 2 of 2



Fiig:

A046b0