NSN 4810-01-110-7090

Solenoid Valve - Page 1 of 2

Thread Class: 2b 1st end



View Online at https://aerobasegroup.com/nsn/4810-01-110-7090

Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Flow Control Device Normal Operation Position:
Closed
Maximum Operating Temp:
180.0 degrees fahrenheit single response
Connection Style:
G5a flar (tube) 1st end
Current Rating In Amps:
0.055
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal tube 1st end
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
105.0 pounds per square inch single response
Thread Size:
0.190 inches 1st end
Voltage In Volts And Current Type:
12.0 dc
Outside Diameter Tube Accommodated:
0.125 inches 1st end
Special Features:
Vent hole 0.125 in.Dia
Material:
Copper alloy or stainless steel
Media For Which Designed:
Gas, inert 2nd response
Style Designator:
Err-090
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a
Unit Of Measure:

NSN 4810-01-110-7090

Solenoid Valve - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A046b0