

View Online at <https://aerobasegroup.com/nsn/4810-01-115-4339>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

100.0 degrees fahrenheit 2nd response

Valve Operation Method:

Electric motor

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

1.562 inches

Maximum Operating Pressure:

600.0 pounds per square inch single response

Voltage In Volts And Current Type:

440.0 ac

Outside Diameter:

6.125 inches all ends

Face To Face Distance:

9.500 inches

Thickness:

0.875 inches all ends

Bolt Hole Diameter:

0.875 inches all ends

Bolt Circle Diameter:

4.500 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.250 inches all ends

Raised Face Diameter:

1.562 inches all ends

Phase:

Three

Frequency In Hertz:

60.0

Material:

Steel comp 416 stem

Material Specification:

Astm a216, grade wcb assn standard single material response body

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0