

View Online at <https://aerobasegroup.com/nsn/4810-01-120-3887>

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Disk

**Flow Control Device Normal Operation Position:**

Closed

**Maximum Operating Temp:**

180.0 degrees fahrenheit single response

**Connection Style:**

G9 plain, optional en (pipe) 1st end

**Current Rating In Amps:**

0.075

**Valve Operation Method:**

Solenoid

**Connection Type:**

Threaded internal pipe 1st end

**Mounting Position:**

Horizontal or vertical

**Inlet/outlet Operating Pressure Differential:**

Between 0.0 pounds per square inch and 280.0 pounds per square inch

**Maximum Operating Pressure:**

500.0 pounds per square inch single response

**Thread Size:**

0.250 inches 1st end

**Voltage In Volts And Current Type:**

120.0 ac

**Phase:**

Single

**Special Features:**

Cexplosion-proof and watertight enclosure; continuous duty coil w/molded class f insulation; 0.500 in. Threaded conduit opening; maximum operating pressure differential for no. 2 fuel oil is 450.0 psi

**Frequency In Hertz:**

60.0

**Material:**

Rubber synthetic seat

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Style Designator:**

Err-090

**Thread Series Designator:**

Npt 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0