

View Online at <https://aerobasegroup.com/nsn/4810-01-120-3887>

Thread Direction:

Right-hand 1st end

Flow Control Device:

Disk

Flow Control Device Normal Operation Position:

Closed

Maximum Operating Temp:

180.0 degrees fahrenheit single response

Connection Style:

G9 plain, optional en (pipe) 1st end

Current Rating In Amps:

0.075

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe 1st end

Mounting Position:

Horizontal or vertical

Inlet/outlet Operating Pressure Differential:

Between 0.0 pounds per square inch and 280.0 pounds per square inch

Maximum Operating Pressure:

500.0 pounds per square inch single response

Thread Size:

0.250 inches 1st end

Voltage In Volts And Current Type:

120.0 ac

Phase:

Single

Special Features:

Cexplosion-proof and watertight enclosure; continuous duty coil w/molded class f insulation; 0.500 in. Threaded conduit opening; maximum operating pressure differential for no. 2 fuel oil is 450.0 psi

Frequency In Hertz:

60.0

Material:

Rubber synthetic seat

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Style Designator:

Err-090

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0