## NSN 4810-01-127-3016

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-127-3016

## Thread Direction:

Right-hand all ends

**Flow Control Device:** 

Poppet

## Flow Control Device Normal Operation Position:

Closed

## **End Application:**

Qf 100 smoke system - pump installation

#### **Connection Style:**

G4 gasket sea (boss) all ends

## Current Rating In Amps:

3.000

Valve Operation Method:

Solenoid

#### Connection Type:

Threaded internal pipe all ends

**Mounting Position:** 

Horizontal

#### Inlet/outlet Operating Pressure Differential:

150.0 pounds per square inch

## Thread Size:

0.500 inches all ends

## Voltage In Volts And Current Type:

24.0 dc

#### **Special Features:**

Material-internal parts are stainless steel; dim 4.000in. Lg, 2.750 in. W, 2.375 in. D; weight - 2.5to 3.0 lbs; two-way

Material:

Copper alloy body

#### Media For Which Designed:

Oil 2nd response

#### Style Designator:

Err-090

#### **Thread Series Designator:**

Npt all ends

#### Furnished Items And Quantity:

1 electrical connector

## Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

Yes - demil/mli

# NSN 4810-01-127-3016

Solenoid Valve - Page 2 of 2

**Fiig:** A046b0

