NSN 4810-01-129-3455

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-129-3455 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet** Flow Control Device Normal Operation Position: Open **Maximum Operating Temp:** 165.0 degrees fahrenheit single response **Connection Style:** G5a flar (tube) 1st end **Current Rating In Amps:** 1.100 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal tube 1st end **Mounting Position:** Horizontal **Maximum Operating Pressure:** 60.0 pounds per square inch single response **Thread Size:** 0.750 inches 1st end **Voltage In Volts And Current Type:** 18.0 dc and 32.0 dc **Outside Diameter Tube Accommodated:** 0.500 inches 1st end Material: Aluminum alloy body Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment:** Anodize **Style Designator:** Err-090 **Thread Series Designator:** Unjf 1st end Shelf Life:

N/a
Unit Of Measure:

NSN 4810-01-129-3455

Solenoid Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0