## NSN 4810-01-136-3576

Solenoid Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4810-01-136-3576

Thread Direction: Right-hand all ends Flow Control Device: Piston Flow Control Device Normal Operation Position: Closed Connection Style: G9 plain, optional en (pipe) all ends Current Rating In Amps: 5.100 Valve Operation Method: Solenoid Connection Type: Threaded internal pipe all ends Mounting Position: Horizontal Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.375 inches all ends Voltage In Volts And Current Type: 115.0 ac
Flow Control Device: Piston Flow Control Device Normal Operation Position: Closed Connection Style: G9 plain, optional en (pipe) all ends Current Rating In Amps: 5.100 Valve Operation Method: Solenoid Connection Type: Threaded internal pipe all ends Mounting Position: Horizontal Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.375 inches all ends Voltage In Volts And Current Type:
Piston Flow Control Device Normal Operation Position: Closed Connection Style: G9 plain, optional en (pipe) all ends Current Rating In Amps: 5.100 Valve Operation Method: Solenoid Connection Type: Threaded internal pipe all ends Mounting Position: Horizontal Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.375 inches all ends Voltage In Volts And Current Type:
Flow Control Device Normal Operation Position: Closed Connection Style: G9 plain, optional en (pipe) all ends Current Rating In Amps: 5.100 Valve Operation Method: Solenoid Connection Type: Threaded internal pipe all ends Mounting Position: Horizontal Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.375 inches all ends Voltage In Volts And Current Type:
Closed  Connection Style: G9 plain, optional en (pipe) all ends  Current Rating In Amps: 5.100  Valve Operation Method: Solenoid  Connection Type: Threaded internal pipe all ends  Mounting Position: Horizontal  Maximum Operating Pressure: 3000.0 pounds per square inch single response  Thread Size: 0.375 inches all ends  Voltage In Volts And Current Type:
Connection Style: G9 plain, optional en (pipe) all ends Current Rating In Amps: 5.100 Valve Operation Method: Solenoid Connection Type: Threaded internal pipe all ends Mounting Position: Horizontal Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.375 inches all ends Voltage In Volts And Current Type:
G9 plain, optional en (pipe) all ends  Current Rating In Amps: 5.100  Valve Operation Method: Solenoid  Connection Type: Threaded internal pipe all ends  Mounting Position: Horizontal  Maximum Operating Pressure: 3000.0 pounds per square inch single response  Thread Size: 0.375 inches all ends  Voltage In Volts And Current Type:
Current Rating In Amps: 5.100  Valve Operation Method: Solenoid  Connection Type: Threaded internal pipe all ends  Mounting Position: Horizontal  Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.375 inches all ends  Voltage In Volts And Current Type:
Valve Operation Method: Solenoid Connection Type: Threaded internal pipe all ends Mounting Position: Horizontal Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.375 inches all ends Voltage In Volts And Current Type:
Valve Operation Method: Solenoid Connection Type: Threaded internal pipe all ends Mounting Position: Horizontal Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.375 inches all ends Voltage In Volts And Current Type:
Solenoid  Connection Type: Threaded internal pipe all ends  Mounting Position: Horizontal  Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.375 inches all ends  Voltage In Volts And Current Type:
Connection Type: Threaded internal pipe all ends Mounting Position: Horizontal Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.375 inches all ends Voltage In Volts And Current Type:
Threaded internal pipe all ends  Mounting Position: Horizontal  Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.375 inches all ends  Voltage In Volts And Current Type:
Mounting Position: Horizontal  Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.375 inches all ends Voltage In Volts And Current Type:
Horizontal  Maximum Operating Pressure: 3000.0 pounds per square inch single response  Thread Size: 0.375 inches all ends  Voltage In Volts And Current Type:
Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.375 inches all ends Voltage In Volts And Current Type:
3000.0 pounds per square inch single response  Thread Size: 0.375 inches all ends  Voltage In Volts And Current Type:
Thread Size: 0.375 inches all ends Voltage In Volts And Current Type:
Thread Size: 0.375 inches all ends Voltage In Volts And Current Type:
Voltage In Volts And Current Type:
-
115.0 ac
Phase:
Single
Special Features:
Media hydraulic fluid
Frequency In Hertz:
60.0
Style Designator:
Err-090
Thread Series Designator:
Nptf all ends
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No.
Fiig:
A046b0