NSN 4810-01-140-0675

Solenoid Valve - Page 1 of 2

Offset Distance: 7.500 inches

Poppet

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4810-01-140-0675

Flow Control Device Normal Operation Position:
Universal
Bolt Hole Quantity:
6 all ends
Valve Operation Method:
Solenoid
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Position:
Horizontal
Valve Size:
2.000 inches
Maximum Operating Pressure:
65.0 pounds per square inch single response
Voltage In Volts And Current Type:
115.0 ac
Outside Diameter:
5.562 inches all ends
Face To Face Distance:
8.000 inches
Thickness:
0.438 inches all ends
First Connection Face To Centerline Distance:
4.000 inches
Bolt Hole Diameter:
0.562 inches all ends
Bolt Circle Diameter:
4.438 inches all ends
Flange Face Design:
Plain all ends
Frequency In Hertz:
60.0
Material:
Nickel alloy flow control device
Material Specification:

Qq-n-288, comp a federal specification single material response flow control device

NSN 4810-01-140-0675

Solenoid Valve - Page 2 of 2



Media For Which Designed:
Water, fresh single response
Style Designator:
Err-090
Specification Data:
81349-mil-v-16556 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0