## NSN 4810-01-140-1865

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-140-1865

#### **Thread Direction:**

Right-hand all ends

## **Flow Control Device:**

Disk

## Flow Control Device Normal Operation Position:

Closed

## Maximum Operating Temp:

200.0 degrees fahrenheit single response

#### **Connection Style:**

G9 plain, optional en (pipe) all ends

## Current Rating In Amps:

0.139

Valve Operation Method:

Solenoid

#### Connection Type:

Threaded internal pipe all ends

**Mounting Position:** 

Horizontal or vertical

## Maximum Operating Pressure:

300.0 pounds per square inch single response

## Thread Size:

1.250 inches all ends

### Voltage In Volts And Current Type:

120.0 ac

Phase:

Single

#### Frequency In Hertz:

60.0

#### Material:

Plastic polytetrafluoroethylene flow control device or rubber butadiene-acrylonitrile class nbr flow control device

#### Media For Which Designed:

Water-oil-gas single response

#### Style Designator:

Err-090

#### **Thread Series Designator:**

Npt all ends

Shelf Life:

N/a

### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 4810-01-140-1865

Solenoid Valve - Page 2 of 2

**Fiig:** A046b0

