## NSN 4810-01-147-8538

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-147-8538

| Thread Class:                                  |
|--|
| 2a all ends                                    |
| Thread Direction:                              |
| Right-hand all ends                            |
| Flow Control Device:                           |
| Disk   |
| Flow Control Device Normal Operation Position: |
| Open   |
| Connection Style:                              |
| G46a plain (tube) 2nd end                      |
| Current Rating In Amps:                        |
| 0.050  |
| Valve Operation Method:                        |
| Solenoid                                       |
| Connection Type:                               |
| Threaded external tube all ends                |
| Mounting Position:                             |
| Horizontal                                     |
| Maximum Operating Pressure:                    |
| 200.0 pounds per square inch single response   |
| Thread Size:                                   |
| 0.438 inches all ends                          |
| Seat Angle:                                    |
| 45.0 degrees 3rd end                           |
| Voltage In Volts And Current Type:             |
| 120.0 ac                                       |
| Phase:   |
| Single   |
| Frequency In Hertz:                            |
| 60.0   |
| Material:                                      |
| Stainless steel body                           |
| Style Designator:                              |
| Err-090  |
| Thread Series Designator:                      |
| Unf all ends                                   |
| Furnished Items And Quantity:                  |
| 2 ferrule and 2 nut                            |
| Shelf Life:                                    |
| N/a  |
| Unit Of Measure:                               |

--

## NSN 4810-01-147-8538

Solenoid Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0