## NSN 4810-01-151-0672

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-151-0672

view Offilite at https://aerobasegroup.com/nsn/4010-01-101-00/2	
Aperture Diameter:	
1.280 inches	
Flow Control Device:	
Poppet	
Flow Control Device Normal Operation Position:	
Open	
Bolt Hole Quantity:	
4 2nd end	
Maximum Operating Temp:	
350.0 degrees fahrenheit single response	
Connection Style:	
G63 beaded (hose) 1st end	
Width:	
1.390 inches 2nd end	
Length:	
2.030 inches 2nd end	
Current Rating In Amps:	
1.000	
Valve Operation Method:	
Solenoid	
Flange Shape:	
Rectangular with holes 2nd end	
Connection Type:	
Unthreaded external tube 1st end	
Mounting Position:	
Horizontal	
Maximum Operating Pressure:	
400.0 pounds per square inch single response	
Voltage In Volts And Current Type:	
30.0 dc	
Bolt Hole Diameter:	
0.234 inches 2nd end	
Center To Center Distance Between Bolt Holes Along Length:	
1.560 inches 2nd end	
Center To Center Distance Between Bolt Holes Along Width:	
0.940 inches 2nd end	
Flange Face Design:	
Plain 2nd end	
Outside Diameter Tube Accommodated:	
0.420 inches 1st end	
Material:	
Chairless steel	

Stainless steel

## NSN 4810-01-151-0672

Solenoid Valve - Page 2 of 2



Style Designator:
Err-090
Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0